

# Omni Vision Inc

2000 Bloomingdale Road  
Units 245-250  
Glendale Heights, IL 60139

## Display Monitor Specialist

Tel: 630-893-1720  
FAX: 630-893-9991  
Web: [www.omnivisionusa.com](http://www.omnivisionusa.com)  
Email: [info@omnivisionusa.com](mailto:info@omnivisionusa.com)

### Industrial TFT Color LCD Display Monitors 15" Chassis Version Models

**Made in the USA**

VGA/SVGA/XGA & NTSC/PAL	Model #	
DC Version - open frame chassis	DM15C1G0-0x... Series	Input: +12 vdc
AC Version - open frame chassis	DM15C4G0-0x... Series	Input: 110/220 VAC
DC Version - with bezel	DM15C1G0-B1... Series	Input: +12 vdc
AC Version - with bezel	DM15C4G0-B1... Series	Input: 110/220 VAC
DC Version - 19" rack mount	DM15C1G0-R1... Series	Input: +12 vdc
AC Version - 19" rack mount	DM15C4G0-R1... Series	Input: 110/220 VAC



## FEATURES

- New LED back light provides extended temperature range
- Standard easy to mount open frame, metal chassis (flanges on all sides)
- Optional - front mount bezel (panel mount ready) with option for NEMA rated applications
- Optional - rack mount (19") panel
- User service controls of brightness, contrast, auto set up, etc
- User service controls accessed in rear standard
- Different models for different input signals - VGA/SVGA/XGA and NTSC or PAL
- Input power flexibility - standard +12 vdc at 2.0 Amps, other DC voltages or auto ranging AC power input from 100-240 VAC @ 47 to 63 Hz
- **RoHS compliant**
- Safety agency compliance - UL, cUL, and others
- Standard model has anti-reflective polycarbonate protective
- Option - resistive touch screens with RS232 or USB interface for Windows and other operating systems

**Omni Vision Inc**  
**2000 Bloomingdale Road**  
**Units 245-250**  
**Glendale Heights, IL 60139**

**Display Monitor Specialist**

Tel: 630-893-1720  
 FAX: 630-893-9991  
 Web: www.omnivisionusa.com  
 Email: info@omnivisionusa.com

**ELECTRICAL & DISPLAY SPECIFICATIONS**

<b>Active Matrix</b>	15" TFT color LCD (381 mm diagonal)
<b>Usable Viewing Area (Size)</b>	11.97" x 8.98" (304.1 x 228.1 mm)
<b>Viewing Angle</b>	Horizontal - right & left 80 degrees Vertical - upper 60 degrees & lower 80 degrees
<b>Dot Pitch</b>	0.297 x 0.297 mm
<b>Max Resolution</b>	1024 x 768
<b>Max Colors</b>	16.2M/262K colors (262K – RGB 6-bit driver)
<b>Response Time</b>	Rise time – 5.7 millisecc (typical) Fall time – 2.3 millisecc (typical)
<b>Horizontal Frequency</b>	31.5 to 54 kHz
<b>Vertical Frequency</b>	56 to 85 Hz
<b>Brightness (full white)</b>	400 nits
<b>Contrast Ratio</b>	700:1 typical
<b>Input Signal</b>	
VGA/SVGA/XGA models	31.4 kHz to 56 kHz @ 60 Hz thru standard analog 15-pin HD mini "D" sub connector
NTSC/PAL models	Standard RCA connector or optional BNC adapter
<b>Power input</b>	
DC voltage input	Standard +12 vdc @ 2 Amps with option to request models With other DC voltage ranging from 9 volts to 48 volts
AC voltage input	Standard 100-240 VAC auto ranging @ 47 to 63 Hz Thru standard IEC-320 connector or 3-wire AC power cord
<b>Temperature</b>	
Operating	-30 to +85 degrees C
Storage	-30 to +85 degrees C

**Mechanical Details**

<b>VGA/SVGA/XGA &amp; NTSC/PAL models</b>		
<b>Open frame – flanges all sides</b>		
DC version	<b>DM15C1G0-01</b>	<b>Drawing 94-414</b>
AC version	<b>DM15C4G0-01</b>	<b>Drawing 94-414</b>
<b>Bezel models (panel mount ready)</b>		
DC version	<b>DM15C1G0-B1</b>	<b>Drawing 94-415</b>
AC version	<b>DM15C4G0-B1</b>	<b>Drawing 94-415</b>
<b>Rack Mount (standard 19" panel)</b>		
DC version	<b>DM15C1G0-R1</b>	<b>Drawing 94-416</b>
AC version	<b>DM15C4G0-R1</b>	<b>Drawing 94-416</b>
<b>Bezel model (NEMA panel mount ready)</b>		
AC version	<b>GT15C4-xx</b>	<b>Drawing 94-420</b>